

## 8 x 2" Dante™ PoE+ powered column speaker



**PoE+** optiZONE noLOGO

<b>Reference</b>	SPC20DP / SPC20DPW
<b>Type</b>	Fixed directivity Column speaker
<b>Amplification</b>	60 W (class D)
<b>Dante™ Receiver</b>	1 (16 / 24 / 32 bit - 44,1 à 96 kHz)
<b>Transducer</b>	8 x 2" fullrange
<b>Peak SPL Capacity (1 m)</b>	117 dB (wide range mode)
<b>Peak SPL Capacity (1 m)</b>	120 dB (long throw mode)
<b>Bandwidth (-10 dB)</b>	120 Hz - 20 kHz
<b>Directivity (H x V)</b>	110° x 12° <i>@500 Hz : 360° x 127°</i> <i>@1000 Hz : 220° x 52°</i> <i>@2000 Hz : 191° x 26°</i> <i>@4000Hz : 110° x 8°</i> <i>@8000Hz : 64° x 8°</i>
<b>Input connector</b>	1 x RJ45
<b>Insert</b>	2 x M6
<b>Dimensions (H x W x D)</b>	484 x 68 x 84 mm
<b>Weight</b>	2,5 kg
<b>Power supply</b>	PoE+ (IEEE 802.3 at)
<b>Accessory</b>	2 axis wall mount (included)
<b>Certification</b>	CE

